

# QuMax for TRB140 with housing

**Integrated outdoor multi band high power LTE directional antenna + place to install Teltonika TRB140 (All-in-one)**

QuMax offers the most powerful directional LTE antenna of all QuWireless antennas. It is dedicated to connections with long distance to base station. It is designed to have Teltonika **TRB140 with housing** router installed inside IP67 enclosure. It is the first choice for fixed installations in industrial environment. This antenna is also compatible with TRB141, TRB142, TRB143 and TRB145.

**4G**  
LTE  
694-2700MHz  
6 dBi  
DIRECTIONAL  
IP 67  
-40° TO +80°

ALL ANTENNAS AND TELTONIKA  
ROUTER INTEGRATED **IN ONE**  
ENCLOSURE



OUTDOOR ANTENNA WORKS IN **ANY**  
WEATHER CONDITIONS, IP67



ANTENNA **PERFECTLY MATCHED** WITH  
THE ROUTER



MADE IN **EUROPE**



## LTE ANTENNA SPECIFICATION


FREQUENCY	0.694 - 0.96 GHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
SUPPORTED LTE/5G BANDS	1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
GAIN	0.694 - 0.96 GHz : 4 dBi 1.7 - 2.2 GHz : 5 dBi 2.2 - 2.7 GHz : 6 dBi
FRONT-TO-BACK	>8 dB
VSWR	<1.30, max <1.80
BEAMWIDTH	90°/90° ±30°
POLARIZATION	Vertical
IMPEDANCE	50 $\Omega$

## MECHANICAL SPECIFICATION


MATERIALS	ABS, aluminum, PTFE, Fiberglass
CONNECTOR TYPE	RJ45
INGRESS PROTECTION	IP67
DIMENSIONS	272 x 276 x 96 mm 10.71 x 10.87 x 3.78 inch
WEIGHT	1.8 kg 3.97 lbs
OPERATING TEMPERATURE	From -40°C to 80°C From -40°F to 176°F
ENCLOSURE RECOMMENDED TIGHTENING TORQUE	0,6 - 0,8 Nm
MAST DIAMETER	25-66mm 0.98-2.60 inch

## PLOTS



VSWR





GAIN





From 700MHz to 900MHz



From 1.71GHz to 2.17GHz



From 2.3GHz to 2.7GHz



## **DIMENSIONS**

