

QuPS2

Outdoor power socket & plug - 2 PIN set

Outdoor power socket & plug 2 PIN set for all cases where the User doesn't want to use Passive PoE powering feature in all QuWireless antennas.



WORKS IN **ANY WEATHER**
CONDITIONS, IP68



CONNECTION **DIRECTLY TO DC**
POWER SOURCE



POWER AND DATA **IN/OUT**
CONNECTION (2 PINS)



MECHANICAL SPECIFICATION

MAXIMUM CURRENT	5A
MAXIMUM VOLTAGE	200V
TEMPERATURE RANGE	-25...70°C
MINIMUM MATING CYCLE	500x
MINIMUM MATING CYCLE FOR MOLEX CONNECTOR	250x
INGRESS PROTECTION	IP68
CONNECTOR TYPE	SP1310/P2I-N, 2 pin Micro-Fit 3.0, 4 pin (2x2)
SP1310 CONNECTOR MATERIALS	Internal contacts material: Brass Internal contact finishing: Gold
MICRO-FIT 3.0 CONNECTOR MATERIALS	Internal contacts material: Phosphor bronze Internal contact finishing: Tin
CABLE TYPE	H05VV-F (0WY) 300/500V 2 cores 0,5mm ² , stranded wire, diameter 8mm, length 150mm
CONNECTOR PINOUT	1 - Power (+) 2 - GND (-)
CONNECTOR FLAMMABILITY CLASS	UL94V-0 flammability class of plastic housing
ROHS COMPLIANCE	Directive 2011/65/EU Directive 2015/863

WEIGHT

0,018 kg
0.039 lbs



Sales email: sales@quwireless.com

Support email: support@quwireless.com

Address: Wireless Instruments Sp. z o.o., ul. Kościuszki 27, 52-116 Iwiny, Poland

WWW.QUWIRELESS.COM

Tel: +48 513 900 416

Website: www.quwireless.com

