

QuSpot for Mikrotik RB912/RB922 I

LTE + Wi-Fi

Integrated multi-band LTE omni antenna + WiFi omni antenna + place to install MikroTik RB912 or RB922 (All-in-one)

QuSpot omnidirectional LTE antenna for **MikroTik RB9xx** is a perfect outdoor device for mobile and fixed installations like CCTV, hotspots, industrial areas, campervans, ships etc.

The set contains IP67, ABS enclosure, LTE MIMO 2x2 and Wi-Fi MIMO 2x2 antennas, RJ45 (Ethernet) port and mast/pole/wall mounting bracket.

If you use MikroTik **RB912 or RB922** with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

4G
LTE**Wi Fi** 6E
694-6000MHz
6 dBi
OMNI
DIRECTIONAL
IP 67
-40° TO +80°

OUTDOOR ANTENNA WORKS IN **ANY**
WEATHER CONDITIONS, IP67



ANTENNA **PERFECTLY MATCHED** WITH
THE ROUTER



WALL OR MAST MOUNTING SYSTEM



MADE IN **EUROPE**



LTE ANTENNA SPECIFICATION

FREQUENCY	694 - 960 MHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
SUPPORTED LTE/5G BANDS	1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
GAIN	694 - 960 MHz : 2 dBi 1.7 - 2.2 GHz : 2 dBi 2.2 - 2.7 GHz : 4 dBi
VSWR	<1.60, max <2.00
BEAMWIDTH	360°/35° ±5°
POLARIZATION	Vertical
IMPEDANCE	50 Ω

WI-FI ANTENNA SPECIFICATION

FREQUENCY	2.40 - 2.50 GHz 5.0 - 7.125 GHz
GAIN	2.40 - 2.50 GHz : 6 dBi 5.0 - 7.125 GHz
VSWR	<1.70, max <2.00
BEAMWIDTH	360°/25° ±5°
POLARIZATION	Vertical
IMPEDANCE	50 Ω

MECHANICAL SPECIFICATION

MATERIALS	ABS, aluminum, PTFE
CONNECTOR TYPE	RJ45
INGRESS PROTECTION	IP67
DIMENSIONS	160 x 160 x 240 mm 6.3 x 6.3 x 9.45 inch
WEIGHT	1.5 kg 3.31 lbs
OPERATING TEMPERATURE	From -40°C to 80°C From -40°F to 176°F
MAST DIAMETER	40-60 mm 1.57-2.36 inch

FREQUENCY BANDS

LTE / 4G GSM	<div> <div>581213141718</div> <div>617 MHz</div> <div> <div>19202627282944</div> <div>960 MHz</div> <div>676885103n81n82n83</div> <div>n89100</div> </div> </div>
LTE / 4G UMTS	<div> <div>123491025</div> <div>1710 MHz</div> <div> <div>333435363739n80</div> <div>2170 MHz</div> <div>n84n86n95n98n101</div> </div> </div>

LTE / 4G WCS DARS

2300
MHz

30

40

n97

2400
MHz

LTE / 4G

2400
MHz

7

38

41

53


69

n90


2700
MHz

PLOTS


VSWSR for Wi-Fi antenna




VSWSR for LTE antenna





Gain for Wi-Fi antenna





Gain for LTE antenna





LTE from 700MHz to 900MHz





LTE from 1.71GHz to 2.17GHz



LTE from 2.3GHz to 2.7GHz



Wi-Fi 2.4 GHz and 5 GHz and 6GHz



DIMENSIONS

