

QuSpot for MikroTik RBM11G | LTE

Integrated multi-band LTE omni antenna + place to install MikroTik RBM11G (All-in-one)

QuSpot omnidirectional LTE 2x2 MIMO antenna for **MikroTik RBM11G** is a perfect outdoor device for mobile and fixed installations like CCTV, hotspots, industrial areas, campervans, ships etc. The set contains IP67 ABS enclosure, LTE antennas, RJ45 (Ethernet) port and mast/pole/wall mounting bracket.

If you use RBM11G with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

4G
LTE
694-2700MHz
4 dBi
**OMNI
DIRECTIONAL**
IP 68
-40° TO +80°

OUTDOOR ANTENNA WORKS IN **ANY
WEATHER CONDITIONS**, IP68



ANTENNA **PERFECTLY MATCHED** WITH
THE ROUTER



WALL OR MAST MOUNTING SYSTEM



MADE IN **EUROPE**



LTE ANTENNA SPECIFICATION

FREQUENCY	694 - 960 MHz 1.7 - 2.2 GHz 2.2 - 2.7 GHz
SUPPORTED LTE/5G BANDS	1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
GAIN	694 - 960 MHz : 2 dBi 1.7 - 2.2 GHz : 2 dBi 2.2 - 2.7 GHz : 4 dBi
VSWR	<1.60, max <2.00
BEAMWIDTH	360°/35° ±5°
POLARIZATION	Vertical
IMPEDANCE	50 Ω

MECHANICAL SPECIFICATION

MATERIALS	ABS, aluminum, PTFE
CONNECTOR TYPE	RJ45
INGRESS PROTECTION	IP68
DIMENSIONS	160 x 160 x 240 mm 6.3 x 6.3 x 9.45 inch
WEIGHT	1.5 kg 3.31 lbs
OPERATING TEMPERATURE	From -40°C to 80°C From -40°F to 176°F
MAST DIAMETER	40-60 mm 1.57-2.36 inch

FREQUENCY BANDS

LTE / 4G GSM	<div>581213141718</div> <div>617 MHz<div>19202627282944</div></div> <div>676885103n81n82n83</div> <div>n89100</div> <div>960 MHz</div>
LTE / 4G UMTS	<div>1710 MHz<div>123491025</div></div> <div>333435363739n80</div> <div>n84n86n95n98n101</div> <div>2170 MHz</div>

LTE / 4G WCS DARS

2300
MHz

30

40

n97

2400
MHz

LTE / 4G

2400
MHz

7

38

41

53


69

n90


2700
MHz

PLOTS



VSWR for LTE antenna




Gain for LTE antenna





LTE from 700MHz to 900MHz



LTE from 1.71GHz to 2.17GHz



LTE from 2.3GHz to 2.7GHz



DIMENSIONS

